ALLNET ALL-CAM2400-NVR-Kit-B / 5MP NVR Kit-Set 5x Bullet HD

EAN CODE

4 0 3 8 8 1 6 1 5 9 9 8 4

Grabador :

- Soporta Ultra 265/H.265/H.264
- Entrada de 4 canales
- Plug & Play
- Soporta 1-canal HDMI, 1-canal VGA
- Salida simultánea HDMI y VGA
- Grabación con una resolución de hasta 2 MP
- 1 disco duro SATA de hasta 10 TB
- Soporta Cloud-Upgrade

Cámaras:

- Funcionalidad diurna/nocturna
- Smart IR, hasta 30m
- Lente óptica de cristal con mayor transmisión de luz
- Ventana antirreflejos IR para aumentar la transmisión de infrarrojos
- 2D/3D DNR (Reducción digital de ruido)
- Streams triples
- IP67

Características técnicas:

Model	**ALL-CAM2400-NVR-Kit-B**

Video/Audio Input	
IP Video Input	4-ch
Network	
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	40Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Recording Resolution	1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	4-ch
Corridor Mode Screen	3/4
Decoding	
Decoding format	Ultra 265/H.265/H.264
Liveview/ Playback	1080p/960p/720p/D1/2CIF/CIF
Capability	4 x 1080p@20, 4 x 720p@30
Hard Disk	
SATA	1 SATA interface
Capacity	up to 10TB for each disk
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Front panel:1 x USB2.0 ; Rear panel:1 x USB2.0
PoE	
Interface	4 independent 100 Mbps PoE network interfaces
Max Power	Max 30W for single port Max 54W in total (13.5W for each)
Supported Standard	IEEE 802.3at, IEEE 802.3af
General	
Power Supply	48V DC Power Consumption: ?5 W(without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ? 90% RH(non-condensing)
Dimensions(W×D×H)	260mm × 240mm × 44mm(10.2"×9.4"×1.7")

Weight (without HDD)	0.93kg (2.05 lb)
Model	**ALL-CAM2400-NVR-Kit-B_Cameras**
Camera	
Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS
Lens	4.0mm@F1.8
Angle of View(H)	86.5°
Shutter	Auto/Manual, 1/6~1/100000 s
Minimum Illumination	Colour: 0.02 Lux (F1.8, AGC ON) 0 Lux with IR on
Digital noise reduction	2D/3D DNR
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:2MP (1920×1080): Max. 30 fps; Sub Stream:720P (1280×720): Max. 30 fps; Third Stream: 4CIF (704×576): Max.30 fps
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2areas
Motion Detection	Up to 4 areas
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP
Compatible Integration	ONVIF(Profile S), API
Interface	

Network	1 RJ45 10M/100M Base-TX Ethernet
General	
Power	12 V DC±25%, PoE (IEEE802.3 af)
	Power consumption: Max 5.5W
Dimensions(L×W×H)	162.9 × 62.4 ×62.7 mm (6.4” × 2.5” × 2.5”)
Weight	0.34kg (0.75 lb)
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity :10%~95% RH(non-condensing)
Ingress Protection	IP67
Reset Button	Supported
Carton	**ALL-CAM2400-NVR-Kit-B**
Dimensions(W×D×H)	340mm × 232mm ×361mm (13.4"× 9.13" ×14.21")
Weight	3.7kg (8.16lb)

Imágenes adicionales

Accesorios

Número de artículo	Denominación
99305	ALLNET ALL951000 Protector contra rayos Cat 6
115427	HDS 2TB Seagate SkyHawk Surveillance *24/7*
115429	HDS 4TB Seagate SkyHawk Surveillance *24/7*
146999	ALLNET PoE USV Backup - USV für Kameras, Accesspoints ALL900

ALLNET GmbH - Maistraße 2 - 82110 Germering - sales@allnet.de - 089 / 894 222 22

Salvo errores y omisiones.